

## MP330、MP330-S



### Product description

3.7 inch LCD, 26 buttons, touch screen  
 Can communicate with most PLCs  
 Password protection, built-in RTC  
 Dynamic display the text  
 Alarm list, button can be defined to many functions  
 With backlight, STN LCD display

### General Specifications:

LCD	STN monochrom
Display area	192*64
Using life	20000 hours, 24 hours running, temperature 25°C
Contrast	Potionmeter adjustable
Language	Chinese, Japanese, English, etc.
Character	Vector, lattice font
Touch panel	Matrix and resistor touch mode
Keys	26 function keys
Screen	64KB FlashROM
Data	1KB SRAM
Download port	RS-232
Communication port	RS-232/422 (MP330-S: RS232/RS485)
Cooling method	Natural air cooling

### Function specifications:

Input voltage	DC24V
Voltage range	DC22V~26V
Consumption current	<140mA
Power off permit	< 10ms ( actual power off time is less than 1s )
Withstand voltage shock	AC1000V, 20mA less than 1 minute
Insulated resistor	>10M, DC500V
Operate temperature	0~50°C
Storage temperature	-20~60°C
Humidity	10%~90%RH ( non-condensation )
Anti-jamming	Interference voltage: 1500Vp-p pulse period:1ms duration:1 minute
Air	Non-corrosive gas
Cooling method	Natural cooling
Dimension	172*121*56.5
Mounting dimension	164*113

### Dimension (unit: mm)

